



Get more in our current issue!

OE Digital Edition
[Click Here](#)
 Current Issue Available Now!



Together, we can deliver under any kind of pressure.



CURRENT NEWS

- First oil off east Africa touted
- CAMAC spuds Nigerian well
- Valemon topside en route to Norway
- BOEM seeks comments on new OCS leasing program
- Seven die in Mexican crane accident
- AWE begins drilling OI-2
- Kashagan production remains frozen
- CLOV in production
- Eni, KMG will explore Isatay in Caspian
- SBM axes tenders with Petrobras

Safety first, for industrial coatings

Written by Del Williams, Power PR Monday, 16 June 2014 14:38

[Print](#) [Email](#)

Rate this item ☆☆☆☆☆ (0 votes)

Industrial facilities turn to safer, more effective inorganic coatings to reduce risk of severe injury and death of coating contractors.

For decades, industrial facilities have measured the effectiveness of a coating by its ability to prevent corrosion, which, of course, is its fundamental purpose. However, with the increasing awareness of the dangers of traditional organic-based coatings and the serious health risks posed to coating contractors, many facility safety managers are specifying safer, inorganic options that now exist on the market.

Coating contractors regularly engage in one of the most hazardous jobs in a plant. Accident reports published by the US Occupational Safety and Health Administration (OSHA), available on the US Department of Labor web site, read like tragic news headlines: "One killed, two injured when paint vapor explodes;" "One employee dies and one is burned in painting flash fire;" "Three employees asphyxiated by paint fumes."

The risks are further exacerbated within confined spaces such as tanks, vessels, silos, storage bins, hoppers, and vaults – common steel structures desperately in need of corrosion protection found in most industrial facilities. Confined spaces are not only known to accumulate toxic, flammable, and even explosive fumes and dust, but the very act of application of traditional coatings presents its own serious risks.

The problem stems from the application of carbon-based coatings, which include commonly-used polymers, polyureas, and urethanes. These coatings off-gas hazardous VOCs and hazardous air pollutants (HAPs) during, and after, application, which can cause irritation of eyes, nose, throat and/or respiratory tract, headaches, nausea, lightheadedness, memory impairment or even unconsciousness to exposed personnel or contractors.

Furthermore, when applied with a spray gun atomized coatings that have low flash points can create a fire or even explode. Given that plural component spray equipment utilizes electrical elements as well as heat, the equipment itself can pose a risk in such an environment.

"Spraying typical coatings inside a tank is dangerous," says Tony Collins, an industrial contractor for 30 years. "Spraying atomizes the toxic, flammable coating material, which can have a flashpoint as low as 70°F, the working temperature inside the tank. This means that if a tool is dropped or a metal object is dragged across the tank and a spark occurs, the fumes can ignite and explode. I'm astonished that it's legal."

The risk is not limited to a single job, unfortunately. Coating contractors consistently exposed to VOCs over time can develop chronic health issues ranging from liver, kidney and nervous system damage to asthma and certain types of cancer.

To address the many risks and improve worker safety, confined space work is regulated by OSHA's Code of Federal Regulations 29 CFR 1910.146. Tragically, as investigation of new accidents continues to illustrate, many of the safety precautions are not followed adequately.

New, inorganic coating options


Fortunately, in the past decade coating technology has changed dramatically. A new category of inorganic chemically bonded phosphate ceramics (CBPCs) has been formulated that emits no VOCs or HAPs during or after application, has no flashpoint, flame spread, or hazardous waste disposal requirements.

Some of these coatings such as EonCoat, contain no toxins of any kind that could cause distress, whether touched, consumed, or inhaled.

The EonCoat ceramic coating consists of two, non-hazardous components that do not interact until applied by a plural component spray gun. Since the components are not mixed and do not meet prior to application, the need for VOC-generating ingredients in the formulation is completely eliminated, as are HAPs.

SESAM™ MARINE

Case study of subsea manifold installation



Watch the webinar video



SAFER, SMARTER, GREENER

DNV-GL

TRENDING WEEK MONTH YEAR

- CLOV in production
- Eni ups African presence
- Shell/Centrica OGUUK board
- Energian named operator offshore Israel
- Seven die in Mexican crane accident
- BP launches Alaska drone program
- Equipment failure reported on Deepwater Nautilus
- Martin Linge taking shape
- Eni, KMG will explore Isatay in Caspian
- SBM axes tenders with Petrobras

MANAGED PRESSURE DRILLING

The New Drilling Convention.
 Your toughest assets are



Contact and collaborate with us at MPDanswers.com >>



Ceramic coatings generate no smoke and have a flame-spread rating of zero, which means that flames will not travel across the surface. In fact, an intense flame can be directly exposed to the coated surface and the substrate will not catch fire unless enough heat is generated to make the substrate behind the coating self-ignite. With no flashpoint, EonCoat cannot ignite or explode during spray application as well.

As for its corrosion resistant properties, ceramic coatings more than pass the test.

In contrast to typical polymer coatings that sit on top of the substrate, EonCoat bonds through a chemical reaction with the substrate, and slight surface oxidation actually improves the reaction. This makes it virtually impossible for corrosion promoters like oxygen and humidity to get behind the coating the way they can with ordinary coatings.

The corrosion barrier is covered by a true ceramic shell, which resists fire, water, abrasion, chemicals, and corrosion.

With the availability of new, safer, inorganic options such as EonCoat on the market, coating experts as well as industrial asset and safety managers can now specify an alternative to traditional carbon-based coatings that will dramatically increase safety without sacrificing corrosion protection.

"If you look at how safety and environmentally-conscious the industry has become, there is no excuse for using toxic, flammable materials where there is another option," states Collins.

For more info, call 252-360-3110; Fax 252-360-3109; email Jim.McBrayer@EonCoat.com; visit www.eoncoat.com; or write to EonCoat at 1704 Park Central Blvd North, Pompano Beach, Florida 33064.

Read more:

[Ceramic coatings can prevent corrosion](#), 1 Oct 2013

Help Oilfield Helping Hands

OilOnline will contribute \$1 to Oilfield Helping Hands for every new profile created on our site.

LEARN & CREATE NOW

PROFILE Share

Read 170 times



Sign Up to see what your friends like.



Published in [OE Products: 2014 / June](#)

Tagged under [safety & security](#) [OSHA](#) [North America](#) [Inspection, repair and maintenance](#)

Related items

- [GOM win for Subsea 7](#)
- [BOEM seeks comments on new OCS leasing program](#)
- [Seven die in Mexican crane accident](#)
- [IHC Merwede bolsters North American presence](#)
- [BP launches Alaska drone program](#)
- [Equipment failure reported on Deepwater Nautilus](#)
- [Kvaerner eyes concrete subsea concepts](#)
- [C-NLOPB offers Jeanne d'Arc basin block](#)
- [Delmar Quick Release - new mooring component](#)
- [FTSI signs JV with Sinopec for hydraulic fracturing](#)

[back to top](#)

CUSTOMER SERVICE

Contact Us
Directory Submission

POLICY

Privacy Policy

ADVERTISING

Advertise With Us
OE@OE