

# CHIEF ENGINEER

Official Publication of The Chief Engineers Association of Chicagoland  
SINCE 1934

September 2019

## HOUSE OF QUE: WATERFRONT EVOLUTION



**Solar Flare: Minnesota Leads Nation in  
Solar Mini-Gardens**

**"Sweating" Pipeline is No Sweat for  
Electric Utility Project**

# “Sweating” Pipeline is No Sweat for Electric Utility Project



The utility protects in use, wet pipeline with an anti-corrosive, water based, ceramic coating with no VOCs or HAPs

When an electric utility in the Southeastern United States sought to protect above-ground natural gas pipeline against corrosion, the goal was to cost effectively do so while minimizing downtime and environmental impact.

Yet in the power and petrochemical industries, protecting above-ground pipeline from corrosion can be a challenge, particularly when the pipeline carries a cooled compressed gas that draws moisture out of a hot or humid external environment. This causes in-use pipeline to continuously drip water, or “sweat,” making adhering a protective coating to the exterior of the pipeline virtually impossible without shutting down the line.

Traditional organic coatings also typically require days or even weeks of facility downtime depending on the project, due to complex surface preparation and application as well as curing times needed between coats. This can be tremendously expensive in terms of lost production as well as shut-down and startup costs.

Utilizing such coatings near people or sensitive areas can also be problematic because they typically involve dangerous Volatile Organic Compounds (VOCs) and Hazardous Air Pollutants (HAPs), as well as clean up using harmful turpentine or mineral spirits.

So when the electric utility chose an anti-corrosive coating

for about 3,500 feet of power plant pipeline in a facility, it was very particular about its selection.

The 30-inch diameter pipeline connects down to smaller diameter pipe that feeds natural gas boilers at the power plant. The boilers provide steam to two 858 MW steam turbines.

Because the power plant is located near a freshwater preserve teeming with wildlife, the electric utility is very attentive to its environmental stewardship.

Accordingly, the electric utility turned to EonCoat, a spray applied inorganic coating from the Raleigh, North Carolina-based company of the same name, for use on the pipeline. EonCoat represents a new category of tough, Chemically Bonded Phosphate Ceramics (CBPCs) that can stop corrosion even when applied on in use, wet, “sweaty” pipeline. This eliminates the need to shut down the pipeline

(Continued on page 30)

MADDOCK INDUSTRIES, INC.



MADDOCKINDUSTRIES.COM (773) 486-1000

Intelligent  
Pumps

DESIGN  
ENVELOPE

Armstrong pumps with integrated connected controls reduce energy as much as 75% compared to traditional constant speed installations, as well as space-saving installation and ease of service.

ARMSTRONG FLUID TECHNOLOGY.COM

ARMSTRONG







for maintenance while also eliminating dangerous VOCs and HAPs.

**In-Use Pipeline Corrosion Protection**

Unlike traditional coatings, the CBPC coating is designed to apply over wet pipe because it is water based, ceramic, and initially porous before setting. This allows any excess water to vent out of the coating during the application process.

In contrast to traditional polymer coatings that sit on top of the substrate, the corrosion resistant CBPC coating bonds through a chemical reaction with the substrate. An alloy lay-

er is formed. This makes it impossible for corrosion promoters like oxygen and humidity to get behind the coating the way they can with ordinary paints.

Although traditional polymer coatings mechanically bond to substrates that have been extensively prepared, if gouged, moisture and oxygen will migrate under the coating's film from all sides of the gouge.

By contrast, the same damage to the ceramic-coated substrate will not spread corrosion on the pipeline because the carbon steel's surface is turned into an alloy of stable oxides.




CALL OUR HOTLINE  
**800.794.5033**  
24 HOURS EMERGENCY SERVICE

We believe in partnership and lifelong relationships

## You Can Count on Quality Service Every Time

- ✓ HVAC/R Installation, Service & Maintenance
- ✓ Ammonia Refrigeration Service & Maintenance
- ✓ Plumbing Installation, Service & Maintenance
- ✓ Systems Integration/BAS Installation
- ✓ Central Plant Services
- ✓ Electrical Installation, Service & Maintenance
- ✓ Fabrication Services
- ✓ MEP Systems Evaluation and much more...

More information: [www.amsmechanicalsystems.com](http://www.amsmechanicalsystems.com)



Once the steel's surface is stable — the way noble metals like gold and silver are stable — it will no longer react with the environment and cannot corrode.

Visible in scanning electron microscope photography, EonCoat does not leave a gap between the steel and the coating because the bond is chemical rather than mechanical. Since there is no gap, even if moisture was to get through to the steel due to a gouge, there is nowhere for the moisture to travel. This effectively stops atmospheric corrosion of power and petrochemical industry pipeline and steel assets.

The corrosion barrier is covered by a ceramic shell that further resists corrosion, water, fire, abrasion, impact, chemicals, and temperatures up to 450 °C. Beyond this, the ceramic shell helps to end the costly maintenance cycle of replacing typical barrier type coatings every few years.

"In power and petrochemical assets such as compressed gas pipelines, if the ceramic shell and alloy layer are ever breached, the ceramic shell acts as a reservoir of phosphate to continually realloy the steel," explains Merrick Alpert, President of EonCoat. "This 'self heals' the breach, depending on its size, and stops the corrosion, if necessary."

This capability, along with the coating's other properties, enables effective corrosion protection for the life of the asset with a single application."

### Easy Application, Environmental Benefits

In the electric utility pipeline project, water jetting the pipeline's exterior was sufficient to clean and prepare the surface for coating, since only a NACE 3 / SSPC-SP 6 /WJ-1 commercial blast cleaning is needed.

The CBPC coating was successfully applied to the exterior of the 'sweating' in use natural gas pipeline outside the facility when atmospheric temperature was 87 °F with 58 percent humidity.


Such CBPC coatings consist of two non-hazardous components that do not interact until applied by a standard industrial plural spray system like those commonly used to apply polyurethane foam or polyurea coatings.

While EonCoat is normally spray applied at a thickness of 20 mils before a topcoat is applied, in this case the CBPC coating was deliberately applied at 25 mils and no topcoat was used to deter mold growth on the pipeline's exterior. The high pH of the inorganic coating tends to retard mold growth when used without a topcoat, even in a hot, humid environment.

Because of the ceramic coating's multiple layers of corrosion protection, and the ability to "self heal" breaches, the power plant is on track to see long-term protection of its pipeline, effectively eliminating the traditional cycle of blasting and recoating during costly shutdowns.

The electric utility also met its environmental goals with this approach. The CBPC coating is inorganic and non-toxic, so there are no VOCs, no HAPs and no odor. The coating is also non-flammable. This enhances safety not only for plant personnel but also for the wildlife of the nearby freshwater preserve.

With atmospheric corrosion a perennial problem for owners or operators of any pipeline that carries compressed gas, whether for natural gas fired power plants or midstream oil and gas companies, the utilization of CBPC coatings that can control corrosion for decades will only help the bottom line and protect the environment.

For more information, call 754-222-4919; visit [www.eoncoat.com](http://www.eoncoat.com); or write to EonCoat, LLC at 551 Pylon Drive, Unit D, Raleigh, NC 27606. 

## HUDSON BOILER & TANK CO.

BOILER & PRESSURE VESSEL REPAIRS -- REFRACTORY REPAIR  
 STACKS -- BREECHINGS -- DUCTS -- STEEL PLATE FABRICATORS & ERECTORS  
 TANKS -- SHOP BUILT AND/OR FIELD ERECTED  
 ASME OR NON-CODE, STATE & CITY LICENSED AND INSURED

**3101 S. State St. ---- Lockport, IL 60441**

(312)666-4780 -- FAX (312)666-5145 -- Website: [www.hudsonboiler.com](http://www.hudsonboiler.com)

Info@Hudsonboiler.com